WST-630 Datasheet Wireless Interlink Smoke Alarm


A.K.A. Wireless Interlink Smoke Alarm + 10 Year Life

Product Image



Model Number	WST-630T
Trade Description	Wireless Interlink Smoke Alarm
Unique ID Code	195610010
Trade Packaging Dimensions WxHxD	136 x 134 x 48 mm
Trade Packaging Weight	31g
Trade Outer Box Quantity	10
Warranty	5 years
Technology	Thermally enhanced optical smoke sensor
Operation AC/DC	DC
Batteries	Includes 2 x non-removable integrated lithium power packs - 10 year life in normal operating conditions
Combined Battery Weight	36g
Product Weight	213g including batteries and mounting plate
Alert Type	Loud 85dB Alarm at 3 metres + red flashing LED
Operating Temperature	+4°C to +38°C
Operating Humidity	Up to 90% RH% non-condensing
Installation Positions	Ceiling or wall mounting
Installation	2 button press for wireless connectivity
Approvals	Certified to EN 14604:2005 by LPCB. Independently tested to RF standard ETSI EN 300 220-2 V2.3.2 (2010-02) by TRaC

Product Dimensions (mm)



Certificate Number	LPCB: 651d/12 CPD: 0832-CPD-1926
Fixing Method	Backplate provides locking facility for security if required
Storage Temperature	-20°C to +60°C
Storage Humidity	Up to 93% RH% non-condensing
Storage Licensing Requirement	N/A
Isotope Activity	N/A
Unit Dimensions	132 x 40.5 mm

Wireless features	
Operating Frequency	868 MHz
Max no. of connected units (network)	50 units
Networking	Multi-directional communication
Compatibility	Compatible with all FireAngel Wi-Safe 2 products
Range	35m (over 200m in clear air)

